

INSTRUCTIONS



PATCHWORK COVER



Materials from Gütermann creativ

(Size 114 x 86 cm)

Sew-all Thread in matching colours; 145 cm wide cotton fabric from Ring a Roses by Gütermann, SUMMER LOFT Collection: 0.20 m of each of pink flower ornament fabric, green-white rose pattern fabric, white-pink flower fabric, pink-white polka-dot fabric, white-pink rose pattern fabric, pink shamrock fabric, pink ornament fabric, pink-white rose pattern fabric, 0.90 m pink meander fabric; 4.20 m pink bias binding

Plus:

1.20 m iron-on batting HH 650,90 cm wide

Cut

From each of the 8 different fabrics 6 squares, $16 \times 16 \text{ cm} = 48 \text{ squares}$. For the back cut $90 \times 120 \text{ cm}$ of each of batting and pink meander fabric.

Instructions

Set out the squares in the desired arrangement with 6 rows each of 8 squares. For the first row lay adjacent squares right sides together, stitch with a 1 cm wide seam; iron the seam allowances to one side. Put all 8 squares together in this way, and follow the same method for the remaining 5 rows. Place the first two rows right sides together, stitch a 1 cm wide seam, iron the seam allowances to one side. Sew all 6 rows together to form a blanket. Lay the batting between the wrong sides of the fabrics for the front and back, to form a sandwich and iron; after ironing, trim the edges accurately. Stitch all around the edges of the 3 layers of fabric to join them together with a long stitch setting, 0.5 cm from the edge. Unfold the bias binding and pin it right side to right side along the edges. Make a fold in the binding at each corner, to form a 45 degree angle to the outer edge. Stitch all around the bias binding



in the ironed fold. Fold the bias binding around the edges with the seam allowance folded inwards and tack; once more make folds at the edges. Iron the binding all the way round. Turn over the end of the bias binding, laying it right sides together on

the binding already sewn on with the seam allowances folded inwards and stitch the seam along the side edge. Trim the seam allowance and turn the binding. Stitch the bias binding securely through all the layers on the right side close to the edge.